


BATTERY CHARGER

SPI1 ⚡ 6/12V 🔋 1A



+++

Battery charger and maintainer

For 6 and 12V batteries up to 32 Ah

Microprocessor controlled

Protection against: Reverse polarity, spark proof and thermal runaway

AGM, Standard, Gel, Calcium, Start n' Stop

Charging status LED

Protective bumpers & hook attachment

Fully automatic and safety shut-off



THE SPI RANGE



TECHNICAL INFORMATION

MODEL	SPI1	SPI2	SPI3	SPI6	SPI10	SPI15	SPI1224
PART NUMBER	940651045*	94065049*	94065050*	94065091*	94065092*	94065189*	94065194*
	* Add letter plug type PLUG EU = C PLUG UK = G PLUG AU = I						
VOLTAGE (DC)	6/12 V	6/12 V	12 V	12 V	12 V	12 V	12/24 V
NOMINAL AC VOLTAGE	230V AC - 50 Hz						
MAX. CHARGING CURRENT	1 A	2 A	3 A	6 A	10 A	15 A	15/10 A
IP RATING	IP54	IP54	IP54	IP20	IP20	IP20	IP20
BATTERY TYPE	Lead-Acid	Lead-Acid	Lead-Acid & Lithium	Lead-Acid	Lead-Acid	Lead-Acid	Lead-Acid
OUTPUT CABLE (cm) (From enclosure to clamp end)	201	185	185	218	218	185	185
WORKING TEMPERATURE	-20° to +50° C						



PACKAGING INFORMATION

MODEL	SPI1	SPI2	SPI3	SPI6	SPI10	SPI15	SPI1224
NET WEIGHT	0,6 kg	1 kg	1 kg	1,4 kg	1,4 kg	1,7 kg	1,7 kg
DIMENSIONS (L x W x H / mm)	195 x 148 x 65	207 x 188 x 75	207 x 188 x 75	238 x 205 x 80	238 x 205 x 80	245 x 225 x 98	245 x 225 x 98

 Schumacher®

Rue de la Baronnerie, 3
4920 Harzé - Belgium

+32 4 388 20 17

info@schumachereurope.com
www.schumachereurope.com

 @schumacherboosters

Since
1947

#passionatesince1947