


BATTERY CHARGER

SPI6 ⚡ **12V** 🔌 **6A**



+++

100% automatic battery charger and maintainer with safety shut-off

AGM, Standard, gel, calcium, Start n' Stop

For 12V batteries up to 130 Ah

Charging status LED

Microprocessor controlled & multi-stage charging

Protective bumpers & hook attachment

Protection against: Reverse polarity, spark proof and thermal runaway

Scrolling digital display languages selection, english, german, french, Italian, spanish



THE SPI RANGE



TECHNICAL INFORMATION

MODEL	SPI1	SPI2	SPI3	SPI6	SPI10	SPI15	SPI1224
PART NUMBER	940651045*	94065049*	94065050*	94065091*	94065092*	94065189*	94065194*
	* Add letter plug type PLUG EU = C PLUG UK = G PLUG AU = I						
VOLTAGE (DC)	6/12 V	6/12 V	12 V	12 V	12 V	12 V	12/24 V
NOMINAL AC VOLTAGE	230V AC - 50 Hz						
MAX. CHARGING CURRENT	1 A	2 A	3 A	6 A	10 A	15 A	15/10 A
IP RATING	IP54	IP54	IP54	IP20	IP20	IP20	IP20
BATTERY TYPE	Lead-Acid	Lead-Acid	Lead-Acid & Lithium	Lead-Acid	Lead-Acid	Lead-Acid	Lead-Acid
OUTPUT CABLE (cm) (From enclosure to clamp end)	201	185	185	218	218	185	185
WORKING TEMPERATURE	-20° to +50° C						



PACKAGING INFORMATION

MODEL	SPI1	SPI2	SPI3	SPI6	SPI10	SPI15	SPI1224
NET WEIGHT	0,6 KG	1 kg	1 kg	1,4 kg	1,4 kg	1,7 kg	1,7 kg
DIMENSIONS (L x W x H / mm)	195 X 148 X 65	207 x 188 x 75	207 x 188 x 75	238 x 205 x 80	238 x 205 x 80	245 x 225 x 98	245 x 225 x 98

 Schumacher®

Rue de la Baronnerie, 3
4920 Harzé - Belgium

+32 4 388 20 17

info@schumachereurope.com
www.schumachereurope.com

 @schumacherboosters

Since
1947

#passionatesince1947