



AGM JUMP STARTER

PROPULSTATION ⚡ 12 V 🔌 800 CA



+++

Robust shell case design 5 mm shatterproof polyethylene

Long and flexible cables with a double insulation and clamps fully insulated

The battery has exceptionally high capacity to accumulate and disperse high-ampere energy

Fully insulated clamps

The connector ensures an optimal recharge of the booster

The blue clamp is fitted with an LED light to make it easier and safer to use, even in the dark.

The 300 A fuse is directly accessible from the outside of the booster



THE PROPULSTATION RANGE



PPS 12V
800 CA



PPS 12V
1200 CA



PPS 12/24V
2400/1200 CA



PPS 12V
6400 CA



PPS 12/24V
3200/1600 CA



PPS 24V
3200 CA

TECHNICAL INFORMATION

MODEL	PPS 12 V 800	PPS 12 V 1200	PPS 12/24 V 2400/1200	PPS 12 V 6400	PPS 12/24 V 3200/1600	PPS 24 V 3200
PART NUMBER	521002	520003	520008	560004	560000	560003
VOLTAGE (DC)	12 V	12 V	12/24 V	12 V	12/24 V	24 V
CRANKING AMPS (CA)	800 A	1200 A	2400/1200 A	6400 A	3200/1600 A	3200 A
CABLE LENGTH	1,55 m	1,55 m	1,35 m	2,10 m	2,10 m	2,10 m
CABLE CROSS SECTION	35 mm ²	50 mm ²	50 mm ²	70 mm ²	70 mm ²	70 mm ²



PACKAGING INFORMATION

MODEL	PPS 12 V 800	PPS 12 V 1200	PPS 12/24 V 2400/1200	PPS 12 V 6400	PPS 12/24 V 3200/1600	PPS 24 V 3200
NET WEIGHT	13,55 kg	17,50 kg	27,90 kg	75 kg	70 kg	70 kg
DIMENSIONS [L x W x h] mm	450 x 170 x 510	450 x 170 x 510	560 x 190 x 610	580 x 510 x 1100	580 x 510 x 1100	580 x 510 x 1100

HOW TO CHOOSE

PART NUMBER	MODEL	VOLTAGE	12 V							24 V						
			<125*	150	175	250	300	350	500	1000+	100	250	500	1000	1500	2000
			HP* = CHECK YOUR ENGINE HP - LEGEND: ■ NORMAL ■ INTENSIVE													
521002	PPS 800	12 V	■	■	■	■										
520003	PPS 1200	12 V	■	■	■	■	■	■								
520008	PPS 2400/1200	12/24 V	■	■	■	■	■	■	■	■	■	■	■	■	■	
560004	PPS 6400	12 V	■	■	■	■	■	■	■	■	■					
560000	PPS 3200/1600	12/24 V	■	■	■	■	■	■	■	■	■	■	■	■	■	
560003	PPS 3200	24V										■	■	■	■	

RELATED PART NUMBER:

DOCKING STATION

DC Vehicle station - with DC cable

AC Workshop station - with charger AC/DC-230/12V

BATTERY CHARGER FOR DOCKING STATION AC

PPS 12V	PPS 12/24 V	12V Mobile	12/24 V Mobile	24 V Mobile
DC12	DC1224	DCM		
AC12	AC1224	ACM		
12V-2 A PN: 522502	12V-3 A PN: 522504	12V-10 A PN: 522510	12V-7 A PN: 522507	12V-10 A PN: 845120-A